

Head Office: "Meherba Plaza" (4th Floor), 33 Topkhana Road, Dhaka-1000, Bangladesh. Cell no: 01729145891 E-mail: glory@dhaka.net, www.glorytradebd.com



Range of application



Product Features

- 1. Integrated structure design ensures lower power consumption, reduced noise, and higher efficiency.
- 2. The cutting knife is independently driven by the motor, with adjustable parameters, resulting in lower noise during operation.
- Features a new rotary hook to eliminate thread breakage and sewing defects, achieving high-quality stitching with a more refined finish.
- 4. Equipped with a standard large touch screen panel for convenient editing and setting of patterns and parameters, making it user-friendly and easy to learn.
- Installed with a lining feeding device that automatically feeds and cuts the lining, enabling easier fabric handling, producing more precise stitching, saving labor, and enhancing efficiency.

Range of Application:

Ideal for straight hole sewing machines for feeding linings in knitted garments.

Technical Parameters

| Specification | Details |
|-----------------------------------|--|
| Model | GLR-1790S-BL-LR |
| Max. Sewing Speed | 4200 rpm |
| Sewing Area | Standard horizontal movement distance 50–80 mm |
| Needle Drive Mode | Pulse motor drive mode |
| Feeding Drive Mode | Pulse motor drive mode |
| Lift the Foot Drive Mode | Pulse motor drive mode |
| Height of Presser Foot | Max. 14 mm |
| Cutter Drive Mode | Pulse motor drive mode |
| Lower Bobbin Thread Catch Device | Standard equipment |
| Bobbin Presser Foot Device | Standard equipment |
| Standard Sewing Pattern | 21 |
| Number of Stored Patterns | 50 |
| Max. Number of Stitches/1 Program | 999 |
| Needle | 134 Nm90 |
| Data Storage Mode | U disk |
| Power Supply | Single phase 110V/220V, Three phase 220V/380V |